

FORM PTO-1390		U.S. DEPARTMENT OF COMMERCE PATENT AND TRADEMARK OFFICE	ATTORNEY'S DOCKET NUMBER
TRANSMITTAL LETTER TO THE UNITED STATES DESIGNATED/ELECTED OFFICE (DO/EO/US) CONCERNING A FILING UNDER 35 U.S.C. 371			1454.1049/RAG 09/807889
INTERNATIONAL APPLICATION NO. PCT/DE99/03207	INTERNATIONAL FILING DATE 5 October 1999	PRIORITY DATE CLAIMED 19 October 1998	
TITLE OF INVENTION NETWORK ARCHITECTURE FOR COMMUNICATION NETWORKS OR DATA NETWORKS			
APPLICANT(S) FOR DO/EO/US Umesh BHAVSAR			
Applicant herewith submits to the United States Designated/Elected Office (DO/EO/US) the following items and other information:			
<ol style="list-style-type: none">1. <input checked="" type="checkbox"/> This is a FIRST submission of items concerning a filing under 35 U.S.C. 371.2. <input checked="" type="checkbox"/> This is an express request to immediately begin national examination procedures (35 U.S.C. 371(f)).3. <input type="checkbox"/> The US has been elected by the expiration of 19 months from the priority date (PCT Article 31).4. <input checked="" type="checkbox"/> A copy of the International Application as filed (35 U.S.C. 371(c)(2))<ol style="list-style-type: none">a. <input checked="" type="checkbox"/> is transmitted herewith (required only if not transmitted by the International Bureau).b. <input type="checkbox"/> has been transmitted by the International Bureau.c. <input type="checkbox"/> is not required, as the application was filed in the United States Receiving Office (RO/US).5. <input checked="" type="checkbox"/> A translation of the International Application into English (35 U.S.C. 371(c)(2)).6. <input checked="" type="checkbox"/> Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371(c)(3))<ol style="list-style-type: none">a. <input checked="" type="checkbox"/> are transmitted herewith (required only if not transmitted by the International Bureau).b. <input type="checkbox"/> have been transmitted by the International Bureau.c. <input type="checkbox"/> is not required, as the application was filed in the United States Receiving Office (RO/US).7. <input checked="" type="checkbox"/> A translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371(c)(3)).8. <input checked="" type="checkbox"/> An oath or declaration of the inventor (35 U.S.C. 371(c)(4)).9. <input type="checkbox"/> A translation of the Annexes to the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371(c)(5)).			
Items 10-15 below concern document(s) or information included:			
<ol style="list-style-type: none">10. <input checked="" type="checkbox"/> An Information Disclosure Statement Under 37 CFR 1.97 and 1.98.11. <input checked="" type="checkbox"/> An assignment document for recording. Please mail the recorded assignment document to:<ol style="list-style-type: none">a. <input checked="" type="checkbox"/> the person whose signature, name & address appears at the bottom of this document.b. <input type="checkbox"/> the following:12. <input checked="" type="checkbox"/> A preliminary amendment.13. <input checked="" type="checkbox"/> A substitute specification14. <input type="checkbox"/> A change of power of attorney and/or address letter.15. <input checked="" type="checkbox"/> Other items or information: International Preliminary Examination Report with amended claims and International Search Report			

09/807889

JCOS Rec'

CT/PTO

19 APR 2001

2. [X] The U.S. National Fee (35 U.S.C. 371(c)(1)) and other fees as follows:

CLAIMS	(1) FOR	(2) NUMBER FILED	(3) NUMBER EXTRA	(4) RATE	(5) CALCULATIONS
	TOTAL CLAIMS	10 -20 =	0	x \$ 18.00	0.00
	INDEPENDENT CLAIMS	7 -3 =	4	x \$ 80.00	320.00
	MULTIPLE DEPENDENT CLAIM(S) (if applicable)			+ \$270.00	0.00
	BASIC NATIONAL FEE (37 CFR 1.492(a)(1)-(4): <input type="checkbox"/> Neither international preliminary examination fee (37 CFR 1.482) nor international search fee (37 CFR 1.445(a)(2)) paid to USPTO.....\$1,000 <input checked="" type="checkbox"/> International preliminary examination fee (37 C.F.R. 1.482) not paid to USPTO but International Search Report prepared by the EPO or JPO.. . . . \$ 860 <input type="checkbox"/> International preliminary examination fee (37 C.F.R. 1.482) not paid to USPTO but international search fee (37 C.F.R. 1.445(a)(2)) paid to USPTO.....\$ 710 <input type="checkbox"/> International preliminary examination fee paid to USPTO (37 CFR 1.482) but all claims did not satisfy provision of PCT Article 33(1)-(4).....\$ 690 <input type="checkbox"/> International preliminary examination fee paid to USPTO (37 CFR 1.482) and all claims satisfied provisions of PCT Article 33(2) to (4).....\$ 100				860.00
	Surcharge of \$130 for furnishing the National fee or oath or declaration later than <input type="checkbox"/> 20 <input type="checkbox"/> 30 mos. from the earliest claimed priority date (37 CFR 1.482(e)).				0.00
	TOTAL OF ABOVE CALCULATIONS				1,180.00
	Reduction by 1/2 for filing by small entity, if applicable. Affidavit must be filed also. (Note 37 CFR 1.9, 1.27, 1.28.)				
	SUBTOTAL				1,180.00
	Processing fee of \$130 for furnishing the English Translation later than <input type="checkbox"/> 20 <input type="checkbox"/> 30 mos. from the earliest claimed priority date (37 CFR 1.482(f)).				.00
	TOTAL NATIONAL FEE				0.00
	Fee for recording the enclosed assignment (37 CFR 1.21(h)).				40.00
	TOTAL FEES ENCLOSED				1,220.00

- a. [X] A check in the amount of \$ 1,220.00 to cover the above fees is enclosed.
- b. ☐ Please charge my Deposit Account No. 19-3935 in the Amount of \$ to cover the above fees. A duplicate copy of this sheet is enclosed.
- c. [X] The Commissioner is hereby authorized to charge any additional fees which may be required, or credit any overpayment to Deposit Account No. 19-3935. A duplicate copy of this sheet is enclosed.



21171

PATENT TRADEMARK OFFICE

4/19/01

DATE

Richard A. Gollhofer

Richard A. Gollhofer
REGISTRATION NO. 31,106

09/807889

JCOB Rec'd TGT/PTO 19 APR 2001

Docket No. 1454.1049/RAG

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of:

Umesh BHAVSAR et al.

Serial No.: (Unassigned)

Group Art Unit: (Unassigned)

Filed: (Concurrently)

Examiner: (Unassigned)

For: NETWORK ARCHITECTURE FOR COMMUNICATION NETWORK OR
DATA NETWORKS

PRELIMINARY AMENDMENT

Assistant Commissioner for Patents
Washington, D.C. 20231

Sir:

Before examination of the above-identified application, please amend the application as follows:

IN THE TITLE

Change "AND/OR" to --OR--.

IN THE SPECIFICATION

Please REPLACE the pending specification with the SUBSTITUTE SPECIFICATION attached hereto.

IN THE ABSTRACT

Please REPLACE the originally filed Abstract with the enclosed Substitute Abstract.

IN THE CLAIMS

Please CANCEL claims 1-9 without prejudice or disclaimer of any of the subject matter claimed therein and ADD new claims in accordance with the following:

10. (NEW) A network architecture of telecommunications networks, each including at least one subjacent physical network, comprising:

network elements of the telecommunications networks for provision of network functions and network services of the at least one subjacent physical network, service provision of the at least one subjacent physical network being guaranteed for at least one user, and distribution of physical resources of the at least one subjacent physical network and provision of existing services being possible in such a way that the data and telecommunications services associated with the individual users can be processed and used independently and efficiently; and

an additional layer of network elements between the subjacent physical networks, including system-independent interfaces using a uniform logical interface to make available network functions of different subjacent physical sub-networks.

11. (NEW) The architecture as claimed in claim 10, wherein control of the network functions of the different subjacent physical sub-networks is taken over by a distributed operating system.

12. (NEW) The architecture as claimed in claim 11, wherein the uniform logical interface also provides function invocations for function classes, which are converted into at least one of sub-network-specific messages and commands and are forwarded to suitable network elements of the different subjacent physical sub-networks, and can be processed or carried out there.

13. (NEW) The architecture as claimed in claim 12, wherein dynamic integration of new network elements is enabled by a new network element registering network element information with a previously registered network element, which stores the network element information and further distributes the network element information to other network elements.

14. (NEW) The architecture as claimed in claim 13, wherein the dynamic integration of new interfaces of already existing network elements is enabled by one of the existing network elements registering new function information with a suitable different network element, which stores the new function information and further distributes the new function information to other network elements.

15. (NEW) The architecture as claimed in claim 14, wherein identical or similar functions exist which are distributed among a plurality of the network elements.

16. (NEW) The architecture as claimed in claim 15, wherein the selection of a function used for a function invocation is made on a specific network node depending on utilization of concerned network nodes.

17. (NEW) The architecture as claimed in claim 16, wherein the function used in a function invocation can be carried out when distributed among a plurality of the concerned network nodes.

18. (NEW) The architecture as claimed in claim 17, wherein frequently used basic services are available and can be used in all network nodes.

REMARKS

This Preliminary Amendment is submitted to improve the form of the specification as originally-filed. It is respectfully requested that this Preliminary Amendment be entered in the above-referenced application.

In accordance with the foregoing, claims 1-9 have been canceled and claims 10- have been added. Claims 10- are pending and are under consideration.

A substitute specification is also being filed herewith. The substitute specification is accompanied by a marked-up copy of the original specification. No new matter has been added.

If there are any questions regarding these matters, such questions can be addressed by telephone to the undersigned. Otherwise, an early action on the merits is respectfully solicited.

If any further fees are required in connection with the filing of this Preliminary Amendment, please charge same to our Deposit Account No. 19-3935.

Respectfully submitted,

STAAS & HALSEY LLP

By: Richard A. Gollhofer
Richard A. Gollhofer
Registration No. 31,106

700 Eleventh Street, N.W.
Suite 500
Washington, D.C. 20001
(202) 434-1500

Date: 4/19/01

MARKED-UP COPY OF ORIGINAL SPECIFICATION

[Description]

TITLE OF THE INVENTION

[Network architecture for communication networks and/or data networks]

5 NETWORK ARCHITECTURE FOR COMMUNICATION OR DATA NETWORKS

BACKGROUND OF THE INVENTION

The invention relates to a network architecture for various communication [and/or] and data networks, providing value-added services for users.

These communication and data networks may have different physical characteristics.

10 They may differ in terms of the type of access to the network functions provided and in terms of data transmission principles (e.g. the transmission protocols used and corresponding standards). Furthermore, they offer different services for the network user.

15 A physical network is understood below to refer to a conventional data or communications network, such as the circuit-switched fixed network (based on SS# 7, Central Channel Signaling System no. 7), the mobile radio network or a computer network such as the Internet, or a local network LAN, based on a communications protocol such as TCP/IP or Token Ring. The providers of the underlying network functions are referred to below as network operators.

20 A corporate network (internal company network or Intranet) designates below a data or communications network, or a network comprising a plurality of such networks, which is assigned to an organizational unit. It enables communication within this organization and is outwardly shielded [with technical means] by hardware, software or a combination thereof.

25 Network operators and service providers offer network users basic functions and services of the physical networks (basic services). "Value-added services" can be generated through integration of basic services (as a rule) of a network. These value-added services can then be sold directly to the user of the service provider (or to special service integrators, who in turn use basic services of service providers).

In the conventional fixed network and in the mobile radio network, for example, value-added services are implemented in addition to basic services along with conventional voice or

data transmission by [means of] an "Intelligent Network". These value-added services involve, for example, a unique telephone number for a user in the entire network (Universal Personal Number), toll-free telephone numbers (Freephone) or voting by telephone (Televoting). These value-added services are implemented by network elements provided centrally in the network (SSP, Service Switching Point, SCP, Service Control Point, etc). The description of the principles of an intelligent network can be found in the ITU protocol suite Q.12xx.

This decentralized implementation of value-added services in a network produces a number of disadvantages. With high network utilization, the network elements responsible for the services present a bottleneck, since all service requests must pass via these network elements and be processed there. In the case of larger, well-utilized networks, this requires a correspondingly high investment in high-performance hardware, in particular for the centrally-controlling network elements ("bottleneck"), since only these elements can control traffic flow with delay times which remain acceptable.

In addition, high availability of the central network nodes such as the SCP, which is responsible for processing the service requests, must be guaranteed. Failure of a single network node of this type here entails the unavailability of all value-added services of the entire network.

For these reasons, the technology required to provide the value-added services can currently be provided by large network operators only. Smaller operators (e.g. City Carriers) on their own cannot make the investment in the necessary high-cost network elements. Use of the network elements by a plurality of service providers or service integrators is not currently possible, since separation of the different functionalities which are implemented in the central network nodes is not provided.

In addition, the different networks are physically separated from each other. In order to be able to use the services of the networks, a customer must switch between different service providers which, in individual cases, may also result in a change of terminal device. The provision of trans-network communication is possible only by [means of] gateways between the individual networks, whereby a connection must be established for each network gateway (e.g. fixed network to mobile radio network, ISDN to Internet) according to the protocols used on both sides.

SUMMARY OF THE INVENTION

[The] An object of the invention is to indicate a facility for providing existing physical networks, including their basic services, in a uniform manner, while avoiding the aforementioned disadvantages. It should also be possible to integrate value-added services, as a combination of basic services offered in different physical networks. [This object is achieved by a network architecture according to claim 1.]

A new distributed network architecture is introduced in the form of a layer of network elements between already existing physical networks and service providers or users. Said network elements communicate via interfaces not only with each other, but also with the physical networks which are connected to them. This layer, which is implemented by [means of] network elements distributed in the network, enables the network user (and also the service provider) to access the existing network resources available in the physical, subjacent networks. This enables all available basic and value-added services to be used (transparency). The required and generated data (access, billing, traffic measurements, etc) are collected separately according to users or service providers in the relevant physical networks, are managed and made available for further processing. The integration of basic services of different physical networks is thus enabled, along with the uniform provision of basic and value-added services of the different physical networks.

Furthermore, network elements of the extended architecture can provide special services to control the networks, in particular central services such as naming, trading or security functions. This provision may occur either separately, in separate network elements, or in the network elements which also provide the general services.

The existing functionality of a central network element can therefore be distributed among a plurality of network elements of the same type. This produces a network architecture which can deal in a flexible manner with changes in the requirements of operators and users. Furthermore, this architecture is characterized by substantially higher reliability, availability and fault tolerance. [Advantageous designs and further developments are indicated in the subclaims.]

The network elements are interconnected by available data networks such as the Internet. Required information is exchanged via this network. The interworking and exchange

of information are controlled by a distributed network operating system, which resides in the individual network elements. The bidirectional transaction principle ensures that changes are reliably carried out. The principle of distributed operating systems is already known to the person skilled in the art.

5 This structure enables flexible integration of services of different networks, whereby new services and value-added services can be offered to users. A network element (client) forwards invocations of network functions to executing network elements (server) for this purpose.

10 In an advantageous embodiment of the invention, the interfaces with subjacent physical networks are standardized. The interworking of the individual network elements is thereby substantially simplified, so that technical agreement of service providers, network operators and the additional service integrators is no longer required. New physical networks, network elements or basic and value-added services can therefore also be readily integrated.

15 In a further embodiment of the invention, standardized function invocations are made available at the interface with the physical networks. This reduces service implementation costs. The term "function class" is understood as a logical combination of a plurality of function invocations which serve a specific purpose. Examples of these are e.g. 'Connection Management', 'Port Management', 'Quality of Service Management' or 'Event Monitoring'. These function invocations are then in turn converted into system-specific messages and
20 commands and are carried out in the corresponding network elements.

'Plug & Play' is now a known principle. In the architecture described, this [means that] makes it possible for a new network element [can] to be incorporated into the existing network structure without major adaptations. Dynamic integration occurs automatically, through registration of functions, function classes and network elements on adjacent network
25 elements. For example, this information can then be distributed in a short time throughout the entire network by [means of] a 'broadcast' method. Registration can also take place on a special network element designated for this purpose, which is then responsible for the network-wide distribution and/or administration of the information. This principle can be applied not only to individual physical networks or network elements, but similarly to the functions and
30 services implemented in these network elements.

A fundamental design of the invention contains the distribution of network functions in the network elements. On the one hand, a high level of resilience is achieved through high functional redundancy. This is also achieved through the selection of the network node which processes the invocation. Load distribution in the network can thereby be implemented.

5 Similar functions can also be invoked and executed simultaneously if required in different network elements.

Particularly in the case of frequently used basic network architecture functions (such as address conversion, data administration, service monitoring), efficiency can be enormously increased if the correspondingly required functions are implemented as standard in some or all
10 of the network elements. Thus, the corresponding function invocations no longer need to be routed with substantial outlay throughout the entire network, thereby reducing the load on the executing network elements. The set of 'basic functions' thereby defined is not static, but can be changed and extended at any time.

The present distribution of tasks in existing telecommunications networks in many ways no longer corresponds to current requirements. Smaller service providers and operators are penetrating the market. Along with network operators, service operators and, last but not least, service providers, who maintain direct contact with customers, are interested in a new distribution facility for the required hardware.

The approach on which the invention is based, i.e. the introduction of a distributed
20 architecture and disclosed interfaces, enables flexible and transparent business relationships between the individual operators and operator types. Third-party manufacturers can integrate their services and applications and thus implement additional value-added services. Cost reduction is likewise achieved. Furthermore, customers can use value-added services, integrated from different networks, whereby correct billing vis-à-vis the different network
25 operators and service providers is always ensured. [The invention is explained below with reference to embodiments, wherein:]

BRIEF DESCRIPTION OF THE DRAWINGS

These and other objects and advantages of the present invention will become more apparent and more readily appreciated from the following description of the preferred embodiments, taken in conjunction with the accompanying drawings of which:

5 Figure 1 shows an example of a distributed network architecture with different subjacent physical communication and data networks,

 Figure 2 shows an example of a distributed network architecture with 2 subjacent physical networks and a service integrator and a service provider,

 Figure 3 shows an invocation arriving from an API manager (client), which is
10 forwarded to the executing network node (server),

 Figure 4 shows an interface between the subjacent physical network, and

 Figure 5 shows a possible implementation solution with interfaces with different physical networks, and

 Figure 6 shows an example of distribution of access to the physical network resources by service providers, service integrators and network operators.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

Reference will now be made in detail to the preferred embodiments of the present invention, examples of which are illustrated in the accompanying drawings, wherein like reference numerals refer to like elements throughout. Restrictions in the figures/embodiments
20 are not obligatory for the invention.

 Figure 1 shows a schematic view of a distributed network architecture, which manifests itself in 3 layers. The 'lowest layer' in this figure reveals the widest variety of currently available physical networks. These are data networks (Corporate Networks, Internet) and communication networks (mobile networks, PSTN), and many others are conceivable. In
25 particular, there are currently no connections, or only very inadequate connections, between the individual networks. The middle layer shows the distributed network architecture which is established 'over' the physical networks. The individual physical networks are in each case connected via at least one connection (1) and a suitable interface in a network element (3) to a data network (2). Service integration takes place here. Representation of the data network as

a ring is only one option, the structure of the data network being irrelevant to the invention. This data network contains the essentially similar, distributed network elements (3, 5), which can be adapted in terms of their performance capability requirements. Individual network elements (5) can also be used only to control the network in that they provide services required for this purpose. Other network elements (3) provide communication and interworking with the subjacent physical networks and provide the interfaces required for this purpose. Interworking and exchange of information (e.g. for registration of network elements and functions) is controlled by a distributed network operating system (6). This resides in the individual network elements (3, 5).

The highest 'layer ' contains the network elements of the service providers. These are similarly connected to the data network via suitable interfaces (4). The associated information required at this end (for user authentication, billing, administration of services, etc) is exchanged. This can likewise be carried out in standardized form, thereby guaranteeing significant simplification of communication, even for different service providers and service integrators.

A more closely defined configuration is presented in figure 2 in order to describe the example explained above in more detail.

A user (customer) purchases a value-added service from a service provider, comprising a fixed network service (PSTN, 7b) and a mobile radio service (Mobile Networks, 7a). The basic services are provided (7a, 7b) by two different network operators. These services are jointly offered (8) to the user by a service provider who stores and administers the customer profile in its customer care center (ABC, Administration, Billing, Customer Care Center) and bills the sold services to the customer.

The relevant customer profile information, such as the customer ID, service profile, is forwarded by the service provider to the service integrator via an interface (4) (implemented, for example, by [means of] an API, Application Programming Interface) in order to purchase the relevant service from the service provider, who in turn forwards the relevant sub-profile for the fixed network service and mobile radio service via interfaces (1a, 1b) to the network operator and receives back from the latter, via the same interface, the required information, such as the implemented fixed network number and mobile radio telephone number.

The corresponding network elements (3a, 3b), which are connected to the physical networks of the network operators and which operate the appropriate interfaces (1a, 1b), are activated by the service integrator via a network element (5) using the service parameters requested by the service provider. These interfaces are geared toward the specific requirements of the relevant physical network (see also figure 4).

If the user has not yet been released by the network operators, this is now done by the network operators who carry out the request of the service integrator, and the required basic services and user facilities are set up. The successful setting up of the subscriber is then reported back by the network operator to the service integrator (transaction principle). A suitable network element (3 or 5) of the service integrator receives this acknowledgement, evaluates it, and, with reference to the value-added service requested by the service provider, determines further required network elements (3a or 3b) and forwards the required information via the connecting network (2) to the network elements (3a, 3b) involved. After processing the received information, these elements in turn forward outstanding requests to the corresponding network elements of the network operators, which are located in the basic networks (Mobile Networks, PSTN).

Once all the network operator services which are required for a value-added service of the service provider are released and confirmed via the interfaces (1a, 1b), the service integrator confirms the complete release of the service for a customer ID via the interface (4) to the service provider, who notifies the customer of this release via the interface (8). The value-added service can thus be used by the customer.

Usage-dependent information, which is determined on the basis of usage of the basic services in the network elements of the network operators, is initially forwarded via the interface (1a, 1b) to the service integrators. In the network elements (3a, 3b, 5), this information is collected according to the integrated value-added services supplied to the service provider, is provided with an identifier (user ID, service ID) and forwarded via (4) to the customer care center (ABC). The service provider is thus able to allocate the received information to the relevant customer profile, to evaluate and bill it (8).

Figure 3 shows a section of the new architecture which is set above the physical networks. The figure shows [4] four network elements (SN1 – SN4, Server Nodes) which are

connected via a data network and exchange function invocations and information, controlled by a distributed network operating system.

An API manager resident in one of the network elements (Client) routes network function invocations associated with applications to the executing network elements (Server Nodes). The API manager provides the required routing information throughout the network for this purpose. This information is exchanged between the network elements and its consistency is maintained. Resources distributed throughout the network can thus be used. Load distribution, for example, is thus possible in that the same functions can be activated in a plurality of network elements.

The example shown in the figure contains an application invocation of a value-added service, which contains function invocations for a plurality of sub-functions (x, y, z). However, the first activated network element cannot process the function invocation, since it does not contain the required functions or its capacity is already fully utilized. It forwards the function invocations to an adjacent node, and an application (xyz) can thus be further processed in parallel on, in this example, three different network elements. Network element (SN2) takes over the processing of function part (x), network element (SN3) takes over the processing of (y) and network element (SN4) takes over the processing of (z).

The routing of the individual sub-function invocations to the processing network elements can be controlled by various criteria. The existence of the required function and the utilization of the individual network elements have been indicated here as an example. A further criterion in the distributed network may involve the length of the path to the processing node, and other criteria are conceivable.

Figure 4 describes in detail the interface between a physical network (PSTN) and a network element in the new distributed network architecture.

The interface component (API) is geared toward the specific requirements of the relevant subjacent basic network. It is structured in such a way that it receives the function invocations for a group of system-independent function classes via the interface (2) and converts them into system-specific commands and procedures of the network elements in the physical network. The 'downward' interface of the (API) is accordingly dependent on the subjacent physical network. Examples of protocols which can be used for communication are

MML (Man Machine Language), CCS#7 (Signaling System no. 7), INAP (Intelligent Network Application Part) or DSS1 (Digital Subscriber Signaling System no. 1; EURO ISDN signaling), depending on the physical network. However, the 'upward' interface of the (API) is defined in a uniform manner. The defined function classes may, for example, comprise

5 Connection Management, Port Management, Event Monitoring and Quality of Service Management.

This principle of disclosed, standardized interfaces simplifies the interworking of network operators with service providers and service integrators, particularly in the introduction of new physical networks and the interplay of the different physical networks.

10 The interface with the physical network does not have to exist with one network node only (broken line).

Figure 5 shows a possible structure from the perspective of the physical networks. It shows clearly distinguishable physical networks which, in some cases, already have protocol interfaces between them. However, these interfaces are always restricted to 2 specific physical networks, e.g. from the digital telephone exchange (EWSD) in a fixed network (PSTN) to the Mobile Services Switching Center (MSC) on the mobile radio side via the central channel signaling system no. 7 (SS#7) on one hand to a Corporate Network (CN) and its private exchange (PBX) by [means of] EURO ISDN signaling (DSS1, Digital Subscriber Signaling System no. 1) on the other hand.

This example clearly shows that each interface between the networks requires its own definition based on the requirements of each physical network. With the increasing number of different types of network, this is not possible for all networks. For each newly added network, an interface must be created with all existing networks. In our example, the Corporate Network (CN), for example, has a connection to the mobile radio network (MN)

25 only via the conventional fixed network (PSTN). An integrated service comprising a CN basic service and a mobile radio service would thus be impossible without taking account of PSTN function.

The number of required interfaces can thus be reduced to the number of existing physical networks by [means of] an overlying network architecture. These interfaces (API

30 sets) provide the user with a uniform interface for access to services of the physical networks.

The central exchange (PBX) of an internal Corporate Network (CN), for example, is provided with a "CTI Interface" (CTI I/F, Computer Telephony Integration). This enables a combination of telephony and data administration in the computer, i.e., for example, searching for and dialing a telephone number in a telephone directory which is held and maintained on a PC or organizer, wherein the connection is set up to a second terminal device (normally a telephone).

A fixed network essentially comprises telephone exchanges. The interface can be implemented here in different ways, e.g. by [means of] an interface according to the INAP protocol (INAP I/F, Intelligent Network Application Part) or a Man Machine Language Interface (MML I/F). It will furthermore be clear that a communications protocol can be used in different types of physical network, since the Man Machine Language (MML) protocol can similarly be used in the interface with the exchanges (MSC) in the mobile radio network (MN).

The network elements which are essential for processing service requests are represented in the Intelligent Network (IN), which already represents a network architecture for a fixed network or mobile radio network with additional network nodes for processing function invocations for value-added services. The Service Control Point (SCP) represents the central node computer which evaluates and processes the service and function invocations. This node computer has hitherto also been the central interface with the other physical networks such as the fixed network (PSTN) or mobile radio network (MN). A private SCP interface (private SCP I/F) is a possible interface with this central network node. The IN network architecture is likewise regarded as the basic network.

The Service Management Point (SMP) is responsible for the introduction, provision and maintenance of value-added services. The development of new services, including testing, is carried out in the Service Creation Environment (SCE). The Customer Service Center(CSC) maintains and updates the customer data. An interface with the CSC is provided by the (Service CSC I/F).

The mobile radio network administers its customer data in a Home Location Register (HLR) and a Visitor Location Register (VLR). As in the fixed network (EWSD) and the Intelligent Network (IN), there is a first interface with the switching computer (MSC). A

further interface is provided by [means of] an Mobile Application Part (MAP) protocol similar to the INAP.

Figure 6 again shows an example of a network which represents a distribution of services and resources in 3 layers. The lowest layer contains the network operators, which provide the physical networks (MN, PSTN, Internet, CN) with the basic services. Separated therefrom, the data network (SCN) according to the invention with individual network elements is located in the 'middle' layer. Here, value-added services are generated which can use resources and services of different physical networks, and which are supplied by service integrators to service providers and are offered by the latter. The service providers operate in the 'highest' layer, where they can supply the value-added services, independently of the physical networks and basic functions used, to the user of these services.

List of abbreviations

	ABC	Administration, Billing, Customer Care
	API	Application Programming Interface
	CCS7	Common Channel Signaling System no. 7 (= SS#7)
5	CN	Corporate Network
	CSC	Customer Service Center
	CTI	Computer Telephony Integration
	DSS1	Digital Subscriber Signaling System no. 1; EURO ISDN signaling
	EWSD	Elektronisches Wählsystem Digital [Digital electronic switching system] (<u>Digital</u>
10		<u>electronic switching system</u>)
	HLR	Home Location Register
	I/F	Interface
	IN	Intelligent Network
	INAP	Intelligent Network Application Part
15	ITU	International Telecommunication Union
	MAP	Mobile Application Part
	MML	Man Machine Language
	MN	Mobile network
	MSC	Mobile Services Switching Center
20	PBX	Private Branch Exchange
	PSTN	Public Switched Telephone Network
	SCE	Service Creation Environment
	SCP	Service Control Point
	SMP	Service Management Point
25	SN	Server Node
	SS#7	Central Channel Signaling System no. 7
	VLR	Visitor Location Register

[References: Q.1200, ITU-T General Recommendations on Telephone Switching and Signaling – Intelligent Network (3/93)]

SUBSTITUTE ABSTRACT

A layer of network elements is provided between already existing physical networks and service providers or users. The network elements communicate via interfaces not only with each other, but also with the physical networks which are connected to them. This layer, which is implemented by network elements distributed in the network, enables the network user to access the existing network resources available in the physical, subjacent networks. This enables all available basic and value-added services to be used. The required and generated data are collected separately according to users or service providers in the relevant physical networks, and are managed and made available for further processing.

5
1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
220

SUBSTITUTE SPECIFICATION

TITLE OF THE INVENTION

NETWORK ARCHITECTURE FOR COMMUNICATION OR DATA NETWORKS

BACKGROUND OF THE INVENTION

5 The invention relates to a network architecture for various communication and data networks, providing value-added services for users.

 These communication and data networks may have different physical characteristics. They may differ in terms of the type of access to the network functions provided and in terms of data transmission principles (e.g. the transmission protocols used and corresponding standards). Furthermore, they offer different services for the network user.

 A physical network is understood below to refer to a conventional data or communications network, such as the circuit-switched fixed network (based on SS# 7, Central Channel Signaling System no. 7), the mobile radio network or a computer network such as the Internet, or a local network LAN, based on a communications protocol such as TCP/IP or Token Ring. The providers of the underlying network functions are referred to below as network operators.

 A corporate network (internal company network or Intranet) designates below a data or communications network, or a network comprising a plurality of such networks, which is assigned to an organizational unit. It enables communication within this organization and is
20 outwardly shielded by hardware, software or a combination thereof.

 Network operators and service providers offer network users basic functions and services of the physical networks (basic services). "Value-added services" can be generated through integration of basic services (as a rule) of a network. These value-added services can then be sold directly to the user of the service provider (or to special service integrators, who
25 in turn use basic services of service providers).

 In the conventional fixed network and in the mobile radio network, for example, value-added services are implemented in addition to basic services along with conventional voice or

data transmission by an "Intelligent Network". These value-added services involve, for example, a unique telephone number for a user in the entire network (Universal Personal Number), toll-free telephone numbers (Freephone) or voting by telephone (Televoting). These value-added services are implemented by network elements provided centrally in the network (SSP, Service Switching Point, SCP, Service Control Point, etc). The description of the principles of an intelligent network can be found in the ITU protocol suite Q.12xx.

This decentralized implementation of value-added services in a network produces a number of disadvantages. With high network utilization, the network elements responsible for the services present a bottleneck, since all service requests must pass via these network elements and be processed there. In the case of larger, well-utilized networks, this requires a correspondingly high investment in high-performance hardware, in particular for the centrally-controlling network elements ("bottleneck"), since only these elements can control traffic flow with delay times which remain acceptable.

In addition, high availability of the central network nodes such as the SCP, which is responsible for processing the service requests, must be guaranteed. Failure of a single network node of this type here entails the unavailability of all value-added services of the entire network.

For these reasons, the technology required to provide the value-added services can currently be provided by large network operators only. Smaller operators (e.g. City Carriers) on their own cannot make the investment in the necessary high-cost network elements. Use of the network elements by a plurality of service providers or service integrators is not currently possible, since separation of the different functionalities which are implemented in the central network nodes is not provided.

In addition, the different networks are physically separated from each other. In order to be able to use the services of the networks, a customer must switch between different service providers which, in individual cases, may also result in a change of terminal device. The provision of trans-network communication is possible only by gateways between the individual networks, whereby a connection must be established for each network gateway (e.g. fixed network to mobile radio network, ISDN to Internet) according to the protocols used on both sides.

SUMMARY OF THE INVENTION

An object of the invention is to indicate a facility for providing existing physical networks, including their basic services, in a uniform manner, while avoiding the aforementioned disadvantages. It should also be possible to integrate value-added services, as a combination of basic services offered in different physical networks.

A new distributed network architecture is introduced in the form of a layer of network elements between already existing physical networks and service providers or users. Said network elements communicate via interfaces not only with each other, but also with the physical networks which are connected to them. This layer, which is implemented by network elements distributed in the network, enables the network user (and also the service provider) to access the existing network resources available in the physical, subjacent networks. This enables all available basic and value-added services to be used (transparency). The required and generated data (access, billing, traffic measurements, etc) are collected separately according to users or service providers in the relevant physical networks, are managed and made available for further processing. The integration of basic services of different physical networks is thus enabled, along with the uniform provision of basic and value-added services of the different physical networks.

Furthermore, network elements of the extended architecture can provide special services to control the networks, in particular central services such as naming, trading or security functions. This provision may occur either separately, in separate network elements, or in the network elements which also provide the general services.

The existing functionality of a central network element can therefore be distributed among a plurality of network elements of the same type. This produces a network architecture which can deal in a flexible manner with changes in the requirements of operators and users. Furthermore, this architecture is characterized by substantially higher reliability, availability and fault tolerance.

The network elements are interconnected by available data networks such as the Internet. Required information is exchanged via this network. The interworking and exchange of information are controlled by a distributed network operating system, which resides in the individual network elements. The bidirectional transaction principle ensures that changes are

reliably carried out. The principle of distributed operating systems is already known to the person skilled in the art.

This structure enables flexible integration of services of different networks, whereby new services and value-added services can be offered to users. A network element (client) forwards invocations of network functions to executing network elements (server) for this purpose.

In an advantageous embodiment of the invention, the interfaces with subjacent physical networks are standardized. The interworking of the individual network elements is thereby substantially simplified, so that technical agreement of service providers, network operators and the additional service integrators is no longer required. New physical networks, network elements or basic and value-added services can therefore also be readily integrated.

In a further embodiment of the invention, standardized function invocations are made available at the interface with the physical networks. This reduces service implementation costs. The term "function class" is understood as a logical combination of a plurality of function invocations which serve a specific purpose. Examples of these are e.g. 'Connection Management', 'Port Management', 'Quality of Service Management' or 'Event Monitoring'. These function invocations are then in turn converted into system-specific messages and commands and are carried out in the corresponding network elements.

'Plug & Play' is now a known principle. In the architecture described, this makes it possible for a new network element to be incorporated into the existing network structure without major adaptations. Dynamic integration occurs automatically, through registration of functions, function classes and network elements on adjacent network elements. For example, this information can then be distributed in a short time throughout the entire network by a 'broadcast' method. Registration can also take place on a special network element designated for this purpose, which is then responsible for the network-wide distribution and/or administration of the information. This principle can be applied not only to individual physical networks or network elements, but similarly to the functions and services implemented in these network elements.

A fundamental design of the invention contains the distribution of network functions in the network elements. On the one hand, a high level of resilience is achieved through high

functional redundancy. This is also achieved through the selection of the network node which processes the invocation. Load distribution in the network can thereby be implemented. Similar functions can also be invoked and executed simultaneously if required in different network elements.

5 Particularly in the case of frequently used basic network architecture functions (such as address conversion, data administration, service monitoring), efficiency can be enormously increased if the correspondingly required functions are implemented as standard in some or all of the network elements. Thus, the corresponding function invocations no longer need to be routed with substantial outlay throughout the entire network, thereby reducing the load on the
10 executing network elements. The set of 'basic functions' thereby defined is not static, but can be changed and extended at any time.

The present distribution of tasks in existing telecommunications networks in many ways no longer corresponds to current requirements. Smaller service providers and operators are penetrating the market. Along with network operators, service operators and, last but not least, service providers, who maintain direct contact with customers, are interested in a new distribution facility for the required hardware.

The approach on which the invention is based, i.e. the introduction of a distributed architecture and disclosed interfaces, enables flexible and transparent business relationships between the individual operators and operator types. Third-party manufacturers can integrate their services and applications and thus implement additional value-added services. Cost reduction is likewise achieved. Furthermore, customers can use value-added services, integrated from different networks, whereby correct billing vis-à-vis the different network operators and service providers is always ensured.

BRIEF DESCRIPTION OF THE DRAWINGS

25 These and other objects and advantages of the present invention will become more apparent and more readily appreciated from the following description of the preferred embodiments, taken in conjunction with the accompanying drawings of which:

Figure 1 shows an example of a distributed network architecture with different subjacent physical communication and data networks,

Figure 2 shows an example of a distributed network architecture with 2 subjacent physical networks and a service integrator and a service provider,

Figure 3 shows an invocation arriving from an API manager (client), which is forwarded to the executing network node (server),

Figure 4 shows an interface between the subjacent physical network, and

Figure 5 shows a possible implementation solution with interfaces with different physical networks, and

Figure 6 shows an example of distribution of access to the physical network resources by service providers, service integrators and network operators.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

Reference will now be made in detail to the preferred embodiments of the present invention, examples of which are illustrated in the accompanying drawings, wherein like reference numerals refer to like elements throughout. Restrictions in the figures/embodiments are not obligatory for the invention.

Figure 1 shows a schematic view of a distributed network architecture, which manifests itself in 3 layers. The 'lowest layer' in this figure reveals the widest variety of currently available physical networks. These are data networks (Corporate Networks, Internet) and communication networks (mobile networks, PSTN), and many others are conceivable. In particular, there are currently no connections, or only very inadequate connections, between the individual networks. The middle layer shows the distributed network architecture which is established 'over' the physical networks. The individual physical networks are in each case connected via at least one connection (1) and a suitable interface in a network element (3) to a data network (2). Service integration takes place here. Representation of the data network as a ring is only one option, the structure of the data network being irrelevant to the invention.

This data network contains the essentially similar, distributed network elements (3, 5), which can be adapted in terms of their performance capability requirements. Individual network elements (5) can also be used only to control the network in that they provide services required for this purpose. Other network elements (3) provide communication and interworking with the subjacent physical networks and provide the interfaces required for this purpose.

Interworking and exchange of information (e.g. for registration of network elements and functions) is controlled by a distributed network operating system (6). This resides in the individual network elements (3, 5).

The highest 'layer ' contains the network elements of the service providers. These are similarly connected to the data network via suitable interfaces (4). The associated information required at this end (for user authentication, billing, administration of services, etc) is exchanged. This can likewise be carried out in standardized form, thereby guaranteeing significant simplification of communication, even for different service providers and service integrators.

A more closely defined configuration is presented in figure 2 in order to describe the example explained above in more detail.

A user (customer) purchases a value-added service from a service provider, comprising a fixed network service (PSTN, 7b) and a mobile radio service (Mobile Networks, 7a). The basic services are provided (7a, 7b) by two different network operators. These services are jointly offered (8) to the user by a service provider who stores and administers the customer profile in its customer care center (ABC, Administration, Billing, Customer Care Center) and bills the sold services to the customer.

The relevant customer profile information, such as the customer ID, service profile, is forwarded by the service provider to the service integrator via an interface (4) (implemented, for example, by an API, Application Programming Interface) in order to purchase the relevant service from the service provider, who in turn forwards the relevant sub-profile for the fixed network service and mobile radio service via interfaces (1a, 1b) to the network operator and receives back from the latter, via the same interface, the required information, such as the implemented fixed network number and mobile radio telephone number.

The corresponding network elements (3a, 3b), which are connected to the physical networks of the network operators and which operate the appropriate interfaces (1a, 1b), are activated by the service integrator via a network element (5) using the service parameters requested by the service provider. These interfaces are geared toward the specific requirements of the relevant physical network (see also figure 4).

If the user has not yet been released by the network operators, this is now done by the network operators who carry out the request of the service integrator, and the required basic services and user facilities are set up. The successful setting up of the subscriber is then reported back by the network operator to the service integrator (transaction principle). A suitable network element (3 or 5) of the service integrator receives this acknowledgement, evaluates it, and, with reference to the value-added service requested by the service provider, determines further required network elements (3a or 3b) and forwards the required information via the connecting network (2) to the network elements (3a, 3b) involved. After processing the received information, these elements in turn forward outstanding requests to the corresponding network elements of the network operators, which are located in the basic networks (Mobile Networks, PSTN).

Once all the network operator services which are required for a value-added service of the service provider are released and confirmed via the interfaces (1a, 1b), the service integrator confirms the complete release of the service for a customer ID via the interface (4) to the service provider, who notifies the customer of this release via the interface (8). The value-added service can thus be used by the customer.

Usage-dependent information, which is determined on the basis of usage of the basic services in the network elements of the network operators, is initially forwarded via the interface (1a, 1b) to the service integrators. In the network elements (3a, 3b, 5), this information is collected according to the integrated value-added services supplied to the service provider, is provided with an identifier (user ID, service ID) and forwarded via (4) to the customer care center (ABC). The service provider is thus able to allocate the received information to the relevant customer profile, to evaluate and bill it (8).

Figure 3 shows a section of the new architecture which is set above the physical networks. The figure shows four network elements (SN1 – SN4, Server Nodes) which are connected via a data network and exchange function invocations and information, controlled by a distributed network operating system.

An API manager resident in one of the network elements (Client) routes network function invocations associated with applications to the executing network elements (Server Nodes). The API manager provides the required routing information throughout the network

for this purpose. This information is exchanged between the network elements and its consistency is maintained. Resources distributed throughout the network can thus be used. Load distribution, for example, is thus possible in that the same functions can be activated in a plurality of network elements.

5 The example shown in the figure contains an application invocation of a value-added service, which contains function invocations for a plurality of sub-functions (x, y, z). However, the first activated network element cannot process the function invocation, since it does not contain the required functions or its capacity is already fully utilized. It forwards the function invocations to an adjacent node, and an application (xyz) can thus be further processed
10 in parallel on, in this example, three different network elements. Network element (SN2) takes over the processing of function part (x), network element (SN3) takes over the processing of (y) and network element (SN4) takes over the processing of (z).

The routing of the individual sub-function invocations to the processing network elements can be controlled by various criteria. The existence of the required function and the utilization of the individual network elements have been indicated here as an example. A
15 further criterion in the distributed network may involve the length of the path to the processing node, and other criteria are conceivable.

Figure 4 describes in detail the interface between a physical network (PSTN) and a network element in the new distributed network architecture.

20 The interface component (API) is geared toward the specific requirements of the relevant subjacent basic network. It is structured in such a way that it receives the function invocations for a group of system-independent function classes via the interface (2) and converts them into system-specific commands and procedures of the network elements in the physical network. The 'downward' interface of the (API) is accordingly dependent on the
25 subjacent physical network. Examples of protocols which can be used for communication are MML (Man Machine Language), CCS#7 (Signaling System no. 7), INAP (Intelligent Network Application Part) or DSS1 (Digital Subscriber Signaling System no. 1; EURO ISDN signaling), depending on the physical network. However, the 'upward' interface of the (API) is defined in a uniform manner. The defined function classes may, for example, comprise

Connection Management, Port Management, Event Monitoring and Quality of Service Management.

This principle of disclosed, standardized interfaces simplifies the interworking of network operators with service providers and service integrators, particularly in the introduction of new physical networks and the interplay of the different physical networks. The interface with the physical network does not have to exist with one network node only (broken line).

Figure 5 shows a possible structure from the perspective of the physical networks. It shows clearly distinguishable physical networks which, in some cases, already have protocol interfaces between them. However, these interfaces are always restricted to 2 specific physical networks, e.g. from the digital telephone exchange (EWSD) in a fixed network (PSTN) to the Mobile Services Switching Center (MSC) on the mobile radio side via the central channel signaling system no. 7 (SS#7) on one hand to a Corporate Network (CN) and its private exchange (PBX) by EURO ISDN signaling (DSS1, Digital Subscriber Signaling System no. 1) on the other hand.

This example clearly shows that each interface between the networks requires its own definition based on the requirements of each physical network. With the increasing number of different types of network, this is not possible for all networks. For each newly added network, an interface must be created with all existing networks. In our example, the Corporate Network (CN), for example, has a connection to the mobile radio network (MN) only via the conventional fixed network (PSTN). An integrated service comprising a CN basic service and a mobile radio service would thus be impossible without taking account of PSTN function.

The number of required interfaces can thus be reduced to the number of existing physical networks by an overlying network architecture. These interfaces (API sets) provide the user with a uniform interface for access to services of the physical networks. The central exchange (PBX) of an internal Corporate Network (CN), for example, is provided with a "CTI Interface" (CTI I/F, Computer Telephony Integration). This enables a combination of telephony and data administration in the computer, i.e., for example, searching for and dialing

a telephone number in a telephone directory which is held and maintained on a PC or organizer, wherein the connection is set up to a second terminal device (normally a telephone).

A fixed network essentially comprises telephone exchanges. The interface can be implemented here in different ways, e.g. by an interface according to the INAP protocol (INAP I/F, Intelligent Network Application Part) or a Man Machine Language Interface (MML I/F). It will furthermore be clear that a communications protocol can be used in different types of physical network, since the Man Machine Language (MML) protocol can similarly be used in the interface with the exchanges (MSC) in the mobile radio network (MN).

The network elements which are essential for processing service requests are represented in the Intelligent Network (IN), which already represents a network architecture for a fixed network or mobile radio network with additional network nodes for processing function invocations for value-added services. The Service Control Point (SCP) represents the central node computer which evaluates and processes the service and function invocations. This node computer has hitherto also been the central interface with the other physical networks such as the fixed network (PSTN) or mobile radio network (MN). A private SCP interface (private SCP I/F) is a possible interface with this central network node. The IN network architecture is likewise regarded as the basic network.

The Service Management Point (SMP) is responsible for the introduction, provision and maintenance of value-added services. The development of new services, including testing, is carried out in the Service Creation Environment (SCE). The Customer Service Center (CSC) maintains and updates the customer data. An interface with the CSC is provided by the (Service CSC I/F).

The mobile radio network administers its customer data in a Home Location Register (HLR) and a Visitor Location Register (VLR). As in the fixed network (EWSD) and the Intelligent Network (IN), there is a first interface with the switching computer (MSC). A further interface is provided by an Mobile Application Part (MAP) protocol similar to the INAP.

Figure 6 again shows an example of a network which represents a distribution of services and resources in 3 layers. The lowest layer contains the network operators, which provide the physical networks (MN, PSTN, Internet, CN) with the basic services. Separated

therefrom, the data network (SCN) according to the invention with individual network elements is located in the 'middle' layer. Here, value-added services are generated which can use resources and services of different physical networks, and which are supplied by service integrators to service providers and are offered by the latter. The service providers operate in the 'highest' layer, where they can supply the value-added services, independently of the physical networks and basic functions used, to the user of these services.

List of abbreviations

	ABC	Administration, Billing, Customer Care
	API	Application Programming Interface
	CCS7	Common Channel Signaling System no. 7 (= SS#7)
5	CN	Corporate Network
	CSC	Customer Service Center
	CTI	Computer Telephony Integration
	DSS1	Digital Subscriber Signaling System no. 1; EURO ISDN signaling
	EWSD	Elektronisches Wählsystem Digital (Digital
10		electronic switching system)
	HLR	Home Location Register
	I/F	Interface
	IN	Intelligent Network
	INAP	Intelligent Network Application Part
	ITU	International Telecommunication Union
	MAP	Mobile Application Part
	MML	Man Machine Language
	MN	Mobile network
	MSC	Mobile Services Switching Center
20	PBX	Private Branch Exchange
	PSTN	Public Switched Telephone Network
	SCE	Service Creation Environment
	SCP	Service Control Point
	SMP	Service Management Point
25	SN	Server Node
	SS#7	Central Channel Signaling System no. 7
	VLR	Visitor Location Register

Description

Network architecture for communication networks and/or data networks

5

The invention relates to a network architecture for various communication and/or data networks, providing value-added services for users.

- 10 These communication and data networks may have different physical characteristics. They may differ in terms of the type of access to the network functions provided and in terms of data transmission principles (e.g. the transmission protocols used and corresponding
- 15 standards). Furthermore, they offer different services for the network user.

- A physical network is understood below to refer to a conventional data or communications network, such as
- 20 the circuit-switched fixed network (based on SS# 7, Central Channel Signaling System no. 7), the mobile radio network or a computer network such as the Internet, or a local network LAN, based on a communications protocol such as TCP/IP or Token Ring.
- 25 The providers of the underlying network functions are referred to below as network operators.

- A corporate network (internal company network or Intranet) designates below a data or communications network, or a network comprising a plurality of such
- 30 networks, which is assigned to an organizational unit. It enables communication within this organization and is outwardly shielded with technical means.

- Network operators and service providers offer network
- 35 users basic functions and services of the physical networks (basic services).

"Value-added services" can be generated through integration of basic services (as a rule) of a network.

These value-added services can then be sold directly to the user of the service provider (or to special service integrators, who in turn use basic services of service providers).

5

In the conventional fixed network and in the mobile radio network, for example, value-added services are implemented in addition to basic services along with conventional voice or data transmission by means of an "Intelligent Network".

These value-added services involve, for example, a unique telephone number for a user in the entire network (Universal Personal Number), toll-free telephone numbers (Freephone) or voting by telephone (Televoting).

These value-added services are implemented by network elements provided centrally in the network (SSP, Service Switching Point, SCP, Service Control Point, etc).

The description of the principles of an intelligent network can be found in the ITU protocol suite Q.12xx.

This decentralized implementation of value-added services in a network produces a number of disadvantages.

With high network utilization, the network elements responsible for the services present a bottleneck, since all service requests must pass via these network elements and be processed there. In the case of larger, well-utilized networks, this requires a correspondingly high investment in high-performance hardware, in particular for the centrally-controlling network elements ("bottleneck"), since only these elements can control traffic flow with delay times which remain acceptable.

In addition, high availability of the central network nodes such as the SCP, which is responsible for processing the service requests, must be guaranteed. Failure of a single network node of this type here
5 entails the unavailability of all value-added services of the entire network.

For these reasons, the technology required to provide the value-added services can currently be provided by large network operators only. Smaller operators (e.g. City Carriers) on their own cannot make the investment in the necessary high-cost network elements. Use of the network elements by a plurality of service providers or service integrators is not currently possible, since separation of the different functionalities which are implemented in the central network nodes is not provided.

In addition, the different networks are physically separated from each other. In order to be able to use the services of the networks, a customer must switch between different service providers which, in individual cases, may also result in a change of terminal device.

The provision of trans-network communication is possible only by means of gateways between the individual networks, whereby a connection must be established for each network gateway (e.g. fixed network to mobile radio network, ISDN to Internet) according to the protocols used on both sides.

The object of the invention is to indicate a facility for providing existing physical networks, including their basic services, in a uniform manner, while avoiding the aforementioned disadvantages. It should also be possible to integrate value-added services, as a combination of basic services offered in different physical networks.

This object is achieved by a network architecture according to claim 1.

A new distributed network architecture is introduced in the form of a layer of network elements between already existing physical networks and service providers or users. Said network elements communicate via interfaces not only with each other, but also with the

physical networks which are connected to them. This layer, which is implemented by means of network elements distributed in the network, enables the network user (and also the service provider) to access
5 the existing network resources available in the physical, subjacent networks. This enables all available basic and value-added services to be used (transparency). The required and generated data (access, billing, traffic measurements, etc) are
10 collected separately according to users or service providers in the relevant physical networks, are managed and made available for further processing. The integration of basic services of different physical networks is thus enabled, along with the uniform
15 provision of basic and value-added services of the different physical networks.

Furthermore, network elements of the extended architecture can provide special services to control
20 the networks, in particular central services such as naming, trading or security functions. This provision may occur either separately, in separate network elements, or in the network elements which also provide the general services.

25 The existing functionality of a central network element can therefore be distributed among a plurality of network elements of the same type. This produces a network architecture which can deal in a flexible
30 manner with changes in the requirements of operators and users.

Furthermore, this architecture is characterized by substantially higher reliability, availability and fault tolerance.

35 Advantageous designs and further developments are indicated in the subclaims.

The network elements are interconnected by available data networks such as the Internet. Required information is exchanged via this network. The interworking and exchange of information are controlled
5 by a distributed network operating system, which resides in the individual network elements. The bidirectional transaction principle ensures that changes are reliably carried out.

The principle of distributed operating systems is
10 already known to the person skilled in the art.

This structure enables flexible integration of services of different networks, whereby new services and value-added services can be offered to users. A network
15 element (client) forwards invocations of network functions to executing network elements (server) for this purpose.

In an advantageous embodiment of the invention, the
20 interfaces with subjacent physical networks are standardized. The interworking of the individual network elements is thereby substantially simplified, so that technical agreement of service providers, network operators and the additional service
25 integrators is no longer required. New physical networks, network elements or basic and value-added services can therefore also be readily integrated.

In a further embodiment of the invention, standardized
30 function invocations are made available at the interface with the physical networks. This reduces service implementation costs.

The term "function class" is understood as a logical combination of a plurality of function invocations
35 which serve a specific purpose. Examples of these are e.g. 'Connection Management', 'Port Management', 'Quality of Service Management' or 'Event Monitoring'.

These function invocations are then in turn converted into system-specific messages and commands and are carried out in the corresponding network elements.

5 'Plug & Play' is now a known principle. In the architecture described, this means that a new network element can be incorporated into the existing network structure without major adaptations. Dynamic integration occurs automatically, through registration
10 of functions, function classes and network elements on adjacent network elements. For example, this information can then be distributed in a short time throughout the entire network by means of a 'broadcast' method. Registration can also take place on a special
15 network element designated for this purpose, which is then responsible for the network-wide distribution and/or administration of the information. This principle can be applied not only to individual physical networks or network elements, but similarly to
20 the functions and services implemented in these network elements.

A fundamental design of the invention contains the distribution of network functions in the network
25 elements. On the one hand, a high level of resilience is achieved through high functional redundancy. This is also achieved through the selection of the network node which processes the invocation. Load distribution in the network can thereby be implemented.
30 Similar functions can also be invoked and executed simultaneously if required in different network elements.

Particularly in the case of frequently used basic
35 network architecture functions (such as address conversion, data administration, service monitoring), efficiency can be enormously increased if the

correspondingly required functions are implemented as standard in some or all of the network elements. Thus, the corresponding function invocations no longer need

CONFIDENTIAL

to be routed with substantial outlay throughout the entire network, thereby reducing the load on the executing network elements.

The set of 'basic functions' thereby defined is not
5 static, but can be changed and extended at any time.

The present distribution of tasks in existing telecommunications networks in many ways no longer corresponds to current requirements. Smaller service
10 providers and operators are penetrating the market. Along with network operators, service operators and, last but not least, service providers, who maintain direct contact with customers, are interested in a new distribution facility for the required hardware.

15 The approach on which the invention is based, i.e. the introduction of a distributed architecture and disclosed interfaces, enables flexible and transparent business relationships between the individual operators and operator types. Third-party manufacturers can
20 integrate their services and applications and thus implement additional value-added services. Cost reduction is likewise achieved.

Furthermore, customers can use value-added services,
25 integrated from different networks, whereby correct billing vis-à-vis the different network operators and service providers is always ensured.

The invention is explained below with reference to
30 embodiments, wherein:

Figure 1 shows an example of a distributed network architecture with different subjacent physical communication and data networks,

Figure 2 shows an example of a distributed network
35 architecture with 2 subjacent physical networks and a service integrator and a service provider,

Figure 3 shows an invocation arriving from an API manager (client), which is forwarded to the executing network node (server),

Figure 3 shows an invocation arriving from an API manager (client), which is forwarded to the executing network node (server),

Figure 4 shows an interface between the subjacent physical network, and

Figure 5 shows a possible implementation solution with interfaces with different physical networks, and

5 Figure 6 shows an example of distribution of access to the physical network resources by service providers, service integrators and network operators.

10 Restrictions in the figures/embodiments are not obligatory for the invention.

Figure 1 shows a schematic view of a distributed network architecture, which manifests itself in 3
15 layers. The 'lowest layer' in this figure reveals the widest variety of currently available physical networks. These are data networks (Corporate Networks, Internet) and communication networks (mobile networks, PSTN), and many others are conceivable. In particular,
20 there are currently no connections, or only very inadequate connections, between the individual networks. The middle layer shows the distributed network architecture which is established 'over' the physical networks. The individual physical networks are
25 in each case connected via at least one connection (1) and a suitable interface in a network element (3) to a data network (2). Service integration takes place here. Representation of the data network as a ring is only one option, the structure of the data network being
30 irrelevant to the invention. This data network contains the essentially similar, distributed network elements (3, 5), which can be adapted in terms of their performance capability requirements. Individual network elements (5) can also be used only to control the
35 network in that they provide services required for this purpose. Other network elements (3) provide

communication and interworking with the subjacent physical networks and provide the interfaces required for this purpose.

Interworking and exchange of information (e.g. for registration of network elements and functions) is controlled by a distributed network operating system (6). This resides in the individual network elements (3, 5).

The highest 'layer ' contains the network elements of the service providers. These are similarly connected to the data network via suitable interfaces (4). The associated information required at this end (for user authentication, billing, administration of services, etc) is exchanged. This can likewise be carried out in standardized form, thereby guaranteeing significant simplification of communication, even for different service providers and service integrators.

A more closely defined configuration is presented in figure 2 in order to describe the example explained above in more detail.

A user (customer) purchases a value-added service from a service provider, comprising a fixed network service (PSTN, 7b) and a mobile radio service (Mobile Networks, 7a). The basic services are provided (7a, 7b) by two different network operators. These services are jointly offered (8) to the user by a service provider who stores and administers the customer profile in its customer care center (ABC, Administration, Billing, Customer Care Center) and bills the sold services to the customer.

The relevant customer profile information, such as the customer ID, service profile, is forwarded by the service provider to the service integrator via an interface (4) (implemented, for example, by means of an API, Application Programming Interface) in order to purchase the relevant service from the service provider, who in turn forwards the relevant sub-profile for the fixed network service and mobile radio service via interfaces (1a, 1b) to the network operator and

receives back from the latter, via the same interface, the required information, such as the implemented fixed network number and mobile radio telephone number.

The corresponding network elements (3a, 3b), which are connected to the physical networks of the network operators and which operate the appropriate interfaces (1a, 1b), are activated by the service integrator via a
5 network element (5) using the service parameters requested by the service provider. These interfaces are geared toward the specific requirements of the relevant physical network (see also figure 4).

If the user has not yet been released by the network
10 operators, this is now done by the network operators who carry out the request of the service integrator, and the required basic services and user facilities are set up. The successful setting up of the subscriber is then reported back by the network operator to the
15 service integrator (transaction principle). A suitable network element (3 or 5) of the service integrator receives this acknowledgement, evaluates it, and, with reference to the value-added service requested by the service provider, determines further required network
20 elements (3a or 3b) and forwards the required information via the connecting network (2) to the network elements (3a, 3b) involved.

After processing the received information, these elements in turn forward outstanding requests to the
25 corresponding network elements of the network operators, which are located in the basic networks (Mobile Networks, PSTN).

Once all the network operator services which are required for a value-added service of the service
30 provider are released and confirmed via the interfaces (1a, 1b), the service integrator confirms the complete release of the service for a customer ID via the interface (4) to the service provider, who notifies the customer of this release via the interface (8). The
35 value-added service can thus be used by the customer.

Usage-dependent information, which is determined on the basis of usage of the basic services in the network elements of the network operators, is initially forwarded via the interface (1a,

1b) to the service integrators. In the network elements (3a, 3b, 5), this information is collected according to the integrated value-added services supplied to the service provider, is provided with an identifier (user ID, service ID) and forwarded via (4) to the customer care center (ABC).

The service provider is thus able to allocate the received information to the relevant customer profile, to evaluate and bill it (8).

10

Figure 3 shows a section of the new architecture which is set above the physical networks.

The figure shows 4 network elements (SN1 - SN4, Server Nodes) which are connected via a data network and exchange function invocations and information, controlled by a distributed network operating system.

An API manager resident in one of the network elements (Client) routes network function invocations associated with applications to the executing network elements (Server Nodes). The API manager provides the required routing information throughout the network for this purpose. This information is exchanged between the network elements and its consistency is maintained.

Resources distributed throughout the network can thus be used. Load distribution, for example, is thus possible in that the same functions can be activated in a plurality of network elements.

The example shown in the figure contains an application invocation of a value-added service, which contains function invocations for a plurality of sub-functions (x, y, z). However, the first activated network element cannot process the function invocation, since it does not contain the required functions or its capacity is already fully utilized. It forwards the function invocations to an adjacent node, and an application (xyz) can thus be further processed in parallel on, in this example, three different network elements. Network

element (SN2) takes over the processing of function
part

(x), network element (SN3) takes over the processing of (y) and network element (SN4) takes over the processing of (z).

5 The routing of the individual sub-function invocations to the processing network elements can be controlled by various criteria. The existence of the required function and the utilization of the individual network elements have been indicated here as an example. A further criterion in the distributed network may
10 involve the length of the path to the processing node, and other criteria are conceivable.

15 Figure 4 describes in detail the interface between a physical network (PSTN) and a network element in the new distributed network architecture.

The interface component (API) is geared toward the specific requirements of the relevant subjacent basic network. It is structured in such a way that it receives the function invocations for a group of
20 system-independent function classes via the interface (2) and converts them into system-specific commands and procedures of the network elements in the physical network. The 'downward' interface of the (API) is accordingly dependent on the subjacent physical
25 network. Examples of protocols which can be used for communication are MML (Man Machine Language), CCS#7 (Signaling System no. 7), INAP (Intelligent Network Application Part) or DSS1 (Digital Subscriber Signaling System no. 1; EURO ISDN signaling), depending on the
30 physical network.

However, the 'upward' interface of the (API) is defined in a uniform manner. The defined function classes may, for example, comprise Connection Management, Port Management, Event Monitoring and Quality of Service
35 Management.

This principle of disclosed, standardized interfaces simplifies the interworking of network operators with

service providers and service integrators, particularly in the introduction of new physical networks and the interplay of the different physical networks.

The interface with the physical network does not have to exist with one network node only (broken line).

Figure 5 shows a possible structure from the perspective of the physical networks.

It shows clearly distinguishable physical networks which, in some cases, already have protocol interfaces between them. However, these interfaces are always restricted to 2 specific physical networks, e.g. from the digital telephone exchange (EWSD) in a fixed network (PSTN) to the Mobile Services Switching Center (MSC) on the mobile radio side via the central channel signaling system no. 7 (SS#7) on one hand to a Corporate Network (CN) and its private exchange (PBX) by means of EURO ISDN signaling (DSS1, Digital Subscriber Signaling System no. 1) on the other hand.

This example clearly shows that each interface between the networks requires its own definition based on the requirements of each physical network. With the increasing number of different types of network, this is not possible for all networks. For each newly added network, an interface must be created with all existing networks. In our example, the Corporate Network (CN), for example, has a connection to the mobile radio network (MN) only via the conventional fixed network (PSTN). An integrated service comprising a CN basic service and a mobile radio service would thus be impossible without taking account of PSTN function.

The number of required interfaces can thus be reduced to the number of existing physical networks by means of an overlying network architecture. These interfaces (API sets) provide the user with a uniform interface for access to services of the physical networks. The central exchange (PBX) of an internal Corporate Network (CN), for example, is provided with a "CTI Interface" (CTI I/F, Computer Telephony Integration). This enables

a combination of telephony and data administration in
the computer,

2025 RELEASE UNDER E.O. 14176

i.e., for example, searching for and dialing a telephone number in a telephone directory which is held and maintained on a PC or organizer, wherein the connection is set up to a second terminal device
5 (normally a telephone).

A fixed network essentially comprises telephone exchanges. The interface can be implemented here in different ways, e.g. by means of an interface according to the INAP protocol (INAP I/F, Intelligent Network
10 Application Part) or a Man Machine Language Interface (MML I/F).

It will furthermore be clear that a communications protocol can be used in different types of physical network, since the Man Machine Language (MML) protocol
15 can similarly be used in the interface with the exchanges (MSC) in the mobile radio network (MN).

The network elements which are essential for processing service requests are represented in the Intelligent Network (IN), which already represents a network
20 architecture for a fixed network or mobile radio network with additional network nodes for processing function invocations for value-added services. The Service Control Point (SCP) represents the central node computer which evaluates and processes the service and
25 function invocations. This node computer has hitherto also been the central interface with the other physical networks such as the fixed network (PSTN) or mobile radio network (MN). A private SCP interface (private SCP I/F) is a possible interface with this central
30 network node. The IN network architecture is likewise regarded as the basic network.

The Service Management Point (SMP) is responsible for the introduction, provision and maintenance of value-added services. The development of new services,
35 including testing, is carried out in the Service Creation Environment (SCE). The Customer Service Center

(CSC) maintains and updates the customer data. An interface with the CSC is provided by the (Service CSC I/F).

The mobile radio network administers its customer data in a Home Location Register (HLR) and a Visitor Location Register (VLR). As in the fixed network (EWSD) and the Intelligent Network (IN), there is a first
5 interface with the switching computer (MSC). A further interface is provided by means of an Mobile Application Part (MAP) protocol similar to the INAP.

Figure 6 again shows an example of a network which
10 represents a distribution of services and resources in 3 layers.

The lowest layer contains the network operators, which provide the physical networks (MN, PSTN, Internet, CN) with the basic services.

15 Separated therefrom, the data network (SCN) according to the invention with individual network elements is located in the 'middle' layer. Here, value-added services are generated which can use resources and services of different physical networks, and which are
20 supplied by service integrators to service providers and are offered by the latter.

The service providers operate in the 'highest' layer, where they can supply the value-added services, independently of the physical networks and basic
25 functions used, to the user of these services.

List of abbreviations

	ABC	Administration, Billing, Customer Care
	API	Application Programming Interface
5	CCS7	Common Channel Signaling System no. 7 (= SS#7)
	CN	Corporate Network
	CSC	Customer Service Center
	CTI	Computer Telephony Integration
	DSS1	Digital Subscriber Signaling System no. 1; EURO
10		ISDN signaling
	EWSD	Elektronisches Wählsystem Digital [<i>Digital electronic switching system</i>]
	HLR	Home Location Register
	I/F	Interface
15	IN	Intelligent Network
	INAP	Intelligent Network Application Part
	ITU	International Telecommunication Union
	MAP	Mobile Application Part
	MML	Man Machine Language
20	MN	Mobile network
	MSC	Mobile Services Switching Center
	PBX	Private Branch Exchange
	PSTN	Public Switched Telephone Network
	SCE	Service Creation Environment
25	SCP	Service Control Point
	SMP	Service Management Point
	SN	Server Node
	SS#7	Central Channel Signaling System no. 7
	VLR	Visitor Location Register

30

References:

Q.1200

- ITU-T General Recommendations on Telephone Switching
 35 and Signaling - Intelligent Network (3/93)

Claims

1. A network architecture comprising network elements of telecommunications networks,
- 5 - for the provision of network functions and network services of at least one subjacent physical network which is used,
- for at least one user of this network architecture, and
- 10 - in which the service provision of the at least one physical network being guaranteed for the at least one user, and
- distribution of physical resources of the at least one subjacent physical network and
- 15 provision of existing services being possible in such a way that the data and telecommunications services associated with the individual users can be processed and used independently and efficiently.
- 20 in which, by means of an additional layer of network elements between the subjacent physical networks, the network functions of the different subjacent physical networks are made available by means of a uniform logical interface via system-
- 25 independent interfaces
2. The architecture as claimed in claim 1 characterized in that
- 30 control of the network functions of the different subjacent physical sub-networks is taken over by a distributed operating system.
3. The architecture as claimed in claim 1 or 2, characterized in that
- 35 the logical interface also provides function invocations for function classes, which are

08-11-2000
GR 98 E 2275

- 16a -

DE 009903207

converted into sub-network-specific messages
and/or commands and

AMENDED SHEET

are forwarded to suitable network elements of the physical sub-networks, and can be processed and/or carried out there.

- 5 4. The architecture as claimed in one of the previous claims,
characterized in that
the dynamic integration of new network elements is enabled in that the new network element carries
10 out a registration with a suitable different network element, which stores this information and further distributes it to other network elements.
- 15 5. The architecture as claimed in one of the previous claims,
characterized in that
the dynamic integration of new interfaces of already existing network elements is enabled in
20 that the network element carries out a registration of the new functions with a suitable different network element, which stores this information and further distributes it to other network elements.
- 25 6. The architecture as claimed in one of the previous claims,
characterized in that
identical or similar functions exist which are distributed among a plurality of network elements.
30
- 35 7. The architecture as claimed in claim 6,
characterized in that
the selection of the function used for a function invocation is made on a specific network node depending on the utilization of the network nodes concerned.

8. The architecture as claimed in one of the previous claims,
characterized in that
5 the functions used in a function invocation can be
carried out when distributed among a plurality of
network nodes.

9. The architecture as claimed in one of the previous claims,
characterized in that
frequently used basic services are available and
can be used in all network nodes.
- 5

Abstract

The invention relates to a network architecture for various communication networks and/or data networks, providing value-added services for users.

A new distributed network architecture is introduced in the form of a layer of network elements between already existing physical networks and service providers or users. Said network elements communicate via interfaces not only with each other, but also with the physical networks which are connected to them. This layer, which is implemented by means of network elements distributed in the network, enables the network user to access the existing network resources available in the physical, subjacent networks. This enables all available basic and value-added services to be used. The required and generated data are collected separately according to users or service providers in the relevant physical networks, are managed and made available for further processing.

Figure 2

98E2275
GR 98 P 2913

FIG. 1

1/6




Fig. 1

2/6




Fig. 2

98E2275
GR 98 P 2913

3/6




Fig. 3

98E2275
GR 98 P 2913

4/6





Fig. 4

5/6

Fig. 5



98E2275
GR 98 P 2913

6/6




Fig. 6

Declaration and Power of Attorney For Patent Application

Erklärung Für Patentanmeldungen Mit Vollmacht

German Language Declaration

Als nachstehend benannter Erfinder erkläre ich hiermit an Eides Statt:

dass mein Wohnsitz, meine Postanschrift, und meine Staatsangehörigkeit den im Nachstehenden nach meinem Namen aufgeführten Angaben entsprechen,

dass ich, nach bestem Wissen der ursprüngliche, erste und alleinige Erfinder (falls nachstehend nur ein Name angegeben ist) oder ein ursprünglicher, erster und Miterfinder (falls nachstehend mehrere Namen aufgeführt sind) des Gegenstandes bin, für den dieser Antrag gestellt wird und für den ein Patent beantragt wird für die Erfindung mit dem Titel:

Netzarchitektur fuer Kommunikations- und/oder Datennetze

deren Beschreibung

(zutreffendes ankreuzen)

☐ hier beigefügt ist.

☒ am 05.10.1999 als

PCT internationale Anmeldung

PCT Anmeldeungsnummer PCT/DE99/03207

eingereicht wurde und am _____
abgeändert wurde (falls tatsächlich abgeändert).

Ich bestätige hiermit, dass ich den Inhalt der obigen Patentanmeldung einschliesslich der Ansprüche durchgesehen und verstanden habe, die eventuell durch einen Zusatzantrag wie oben erwähnt abgeändert wurde.

Ich erkenne meine Pflicht zur Offenbarung irgendwelcher Informationen, die für die Prüfung der vorliegenden Anmeldung in Einklang mit Absatz 37, Bundesgesetzbuch, Paragraph 1.56(a) von Wichtigkeit sind, an.

Ich beanspruche hiermit ausländische Prioritätsvorteile gemäss Abschnitt 35 der Zivilprozessordnung der Vereinigten Staaten, Paragraph 119 aller unten angegebenen Auslandsanmeldungen für ein Patent oder eine Erfindersurkunde, und habe auch alle Auslandsanmeldungen für ein Patent oder eine Erfindersurkunde nachstehend gekennzeichnet, die ein Anmeldedatum haben, das vor dem Anmeldedatum der Anmeldung liegt, für die Priorität beansprucht wird.

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name,

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

Network architecture for communication networks and/or data networks

the specification of which

(check one)

☐ is attached hereto.

☒ was filed on 05.10.1999 as

PCT international application

PCT Application No. PCT/DE99/03207

and was amended on _____
(if applicable)

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to the examination of this application in accordance with Title 37, Code of Federal Regulations, §1.56(a).

I hereby claim foreign priority benefits under Title 35, United States Code, §119 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

German Language Declaration

Prior foreign applications
Priorität beansprucht

Priority Claimed

19848114.4

DE

19.10.1998

☒

☐

(Number)
(Nummer)

(Country)
(Land)

(Day Month Year Filed)
(Tag Monat Jahr eingereicht)

Yes
Ja

No
Nein

(Number)
(Nummer)

(Country)
(Land)

(Day Month Year Filed)
(Tag Monat Jahr eingereicht)

☐
Yes
Ja

☐
No
Nein

(Number)
(Nummer)

(Country)
(Land)

(Day Month Year Filed)
(Tag Monat Jahr eingereicht)

☐
Yes
Ja

☐
No
Nein

Ich beanspruche hiermit gemäss Absatz 35 der Zivilprozessordnung der Vereinigten Staaten, Paragraph 120, den Vorzug aller unten aufgeführten Anmeldungen und falls der Gegenstand aus jedem Anspruch dieser Anmeldung nicht in einer früheren amerikanischen Patentanmeldung laut dem ersten Paragraphen des Absatzes 35 der Zivilprozessordnung der Vereinigten Staaten, Paragraph 122 offenbart ist, erkenne ich gemäss Absatz 37, Bundesgesetzbuch, Paragraph 1.56(a) meine Pflicht zur Offenbarung von Informationen an, die zwischen dem Anmeldedatum der früheren Anmeldung und dem nationalen oder PCT internationalen Anmeldedatum dieser Anmeldung bekannt geworden sind.

I hereby claim the benefit under Title 35, United States Code, §120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, §122, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, §1.56(a) which occurred between the filing date of the prior application and the national or PCT international filing date of this application.

PCT/DE99/03207

(Application Serial No.)
(Anmeldeseriennummer)

05.10.1999

(Filing Date D, M, Y)
(Anmeldedatum T, M, J)

(Status)
(patentiert, anhangig,
aufgegeben)

(Status)
(patented, pending,
abandoned)

(Application Serial No.)
(Anmeldeseriennummer)

(Filing Date D,M,Y)
(Anmeldedatum T, M; J)

(Status)
(patentiert, anhangig,
aufgeben)

(Status)
(patented, pending,
abandoned)

Ich erkläre hiermit, dass alle von mir in der vorliegenden Erklärung gemachten Angaben nach meinem besten Wissen und Gewissen der vollen Wahrheit entsprechen, und dass ich diese eidesstattliche Erklärung in Kenntnis dessen abgebe, dass wissentlich und vorsätzlich falsche Angaben gemäss Paragraph 1001, Absatz 18 der Zivilprozessordnung der Vereinigten Staaten von Amerika mit Geldstrafe belegt und/oder Gefängnis bestraft werden können, und dass derartig wissentlich und vorsätzlich falsche Angaben die Gültigkeit der vorliegenden Patentanmeldung oder eines darauf erteilten Patentes gefährden können.

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true, and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

German Language Declaration

VERTRETUNGSVOLLMACHT: Als benannter Erfinder beauftrage ich hiermit den nachstehend benannten Patentanwalt (oder die nachstehend benannten Patentanwälte) und/oder Patent-Agenten mit der Verfolgung der vorliegenden Patentanmeldung sowie mit der Abwicklung aller damit verbundenen Geschäfte vor dem Patent- und Warenzeichenamt: (Name und Registrationsnummer anführen)

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith. (list name and registration number)

Customer No. 21171

And I hereby appoint

Telefongespräche bitte richten an:
(Name und Telefonnummer)

Direct Telephone Calls to: (name and telephone number)

Ext. _____

Postanschrift:

Send Correspondence to:

Staas & Halsey LLP
700 Eleventh Street NW, Suite 500 20001 Washington, DC
Telephone: +1 202 434 1500 and Facsimile +1 202 434 1501

or
Customer No. 21171

Voller Name des einzigen oder ursprünglichen Erfinders: UMESH BHAVSAR		Full name of sole or first inventor: UMESH BHAVSAR	
Unterschrift des Erfinders <i>[Signature]</i>	Datum 22 March 01	Inventor's signature <i>[Signature]</i>	Date 22 March 01
Wohnsitz BOCA RATON, FL 33433, UNIT 304, UNITED STATES OF AMERICA		Residence BOCA RATON, FL 33433, UNIT 304, UNITED STATES OF AMERICA	
Staatsangehörigkeit GB		Citizenship GB	
Postanschrift 22075 LAS BRISAS CIRCLE		Post Office Address 22075 LAS BRISAS CIRCLE	
BOCA RATON, FL 33433, UNIT 304		BOCA RATON, FL 33433, UNIT 304	
Voller Name des zweiten Miterfinders (falls zutreffend): JAN HAMANN		Full name of second joint inventor, if any: JAN HAMANN	
Unterschrift des Erfinders <i>[Signature]</i>	Datum 09-03-01	Second inventor's signature <i>[Signature]</i>	Date 09-03-01
Wohnsitz MUENCHEN, DEUTSCHLAND		Residence MUENCHEN, GERMANY	
Staatsangehörigkeit DE		Citizenship DE	
Postanschrift ERLBACHSTR.9 B		Post Office Address ERLBACHSTR.9 B	
81249 MUENCHEN		81249 MUENCHEN	

(Bitte entsprechende Informationen und Unterschriften im Falle von dritten und weiteren Miterfindern angeben).

(Supply similar information and signature for third and subsequent joint inventors).

Voller Name des dritten Miterfinders: Dr. RALF RIEKEN <i>3-00</i>		Full name of third joint inventor: Dr. RALF RIEKEN	
Unterschrift des Erfinders <i>[Signature]</i>	Datum	Inventor's signature <i>[Signature]</i>	Date
Wohnsitz MUENCHEN, DEUTSCHLAND		Residence MUENCHEN, GERMANY <i>DEX</i>	
Staatsangehörigkeit DE		Citizenship DE	
Postanschrift IRMINSULSTR. 12 <i>Malsenstr. 35</i>		Post Office Address IRMINSULSTR. 12 <i>Malsenstr. 35</i>	
81674 MUENCHEN <i>80682 München</i>		81674 MUENCHEN <i>80682 München</i>	
Voller Name des vierten Miterfinders: THOMAS WERNER <i>4-00</i>		Full name of fourth joint inventor: THOMAS WERNER	
Unterschrift des Erfinders <i>[Signature]</i>	Datum <i>2.23.07</i>	Inventor's signature	Date
Wohnsitz MUENCHEN, DEUTSCHLAND		Residence MUENCHEN, GERMANY <i>DEX</i>	
Staatsangehörigkeit DE		Citizenship DE	
Postanschrift LUDWIG-WOERL-WEG 6		Post Office Address LUDWIG-WOERL-WEG 6	
81375 MUENCHEN		81375 MUENCHEN	
Voller Name des fünften Miterfinders:		Full name of fifth joint inventor:	
Unterschrift des Erfinders	Datum	Inventor's signature	Date
Wohnsitz		Residence	
Staatsangehörigkeit		Citizenship	
Postanschrift		Post Office Address	
Voller Name des sechsten Miterfinders:		Full name of sixth joint inventor:	
Unterschrift des Erfinders	Datum	Inventor's signature	Date
Wohnsitz		Residence	
Staatsangehörigkeit		Citizenship	
Postanschrift		Post Office Address	

(Bitte entsprechende Informationen und Unterschriften im Falle von dritten und weiteren Miterfindern angeben).

(Supply similar information and signature for third and subsequent joint inventors).